

# AIR HANDLER TERMINAL UNIT CONTROLLER

## OVERVIEW

The HVAC building automation controls market requires a flexible and economical DDC controller that provides optimum zone control for packaged air handling terminal unit applications.

Efficient Building Automation Corporation's Circon™ **SCC-310-AHC** comes complete with easy-to-configure air handler terminal unit control software, combined with a cost-effective hardware platform to provide exceptional flexibility. Configurable for a variety of applications, the SCC-310-AHC is all you need in a 13 point air handling unit DDC controller.

## APPLICATIONS

The SCC-310-AHC can be used in most two or four-pipe packaged air handler applications. It maintains a constant zone or supply air temperature through configurable, sequenced control of the supply fan, one or two heating sources, one cooling source, and an optional outdoor air damper and exhaust damper or fan.

To optimize energy usage with minimal impact on comfort, an internal schedule allows the SCC-310-AHC to adapt its control sequence to occupied, unoccupied or standby setpoints, and implement demand limiting from a supervisory control source.

A versatile side loop provides three styles of control for a wide range of equipment including unit heater, baseboard heater, exhaust fan, lighting, maintaining space or duct static pressure, and more. The side loop together with other unused I/O can save the cost of additional controllers for simple applications.

EBAC's free Windows® based configuration software for the SCC-310-AHC is fully compatible with Echelon® Corporation's LNS® and Tridium® Inc.'s Niagara<sup>AX</sup>®.

## ORDERING INFORMATION

Part number: 10-0435



## FEATURES

- LonMark Certified, with easy-to-use LNS plug-ins for seamless integration into interoperable LonWorks® networks
- Fast and easy-to-use Tridium Niagara<sup>AX</sup> wizards for seamless integration into interoperable Niagara networks
- Easily mounts directly inside air handler enclosure
- 5 relay and 2 analog outputs simplify connecting to a variety of digital, floating and analog-controlled actuators for standard air handler units
- 5 resistive inputs for space temperature (required), supply air temperature, mixed air temperature, setpoint adjust, fan, filter window and occupancy sensors
- Analog input enables demand control ventilation or dehumidification control
- Side loop provides independent control for additional simple HVAC equipment
- Onboard soft clock, scheduling, and trending to decrease costs and increase flexibility
- Transmits alarms for local or remote annunciation



CIRCON

**SPECIFICATIONS**

**I/O CAPABILITY**

6 Inputs: Five 10 kΩ thermistor, Precon curve: Type II model 24 or Type III model 3, or dry contact  
 One voltage, 0-10 VDC

2 Analog Outputs: 0-10 VDC, maximum drive of 100 mA per output

5 Digital Outputs: Dry contact relay: 2.0 A maximum at 24 VAC or 24 VDC

**COMMUNICATIONS**

Transceiver: Echelon Free Topology Transceiver (FTT-10A @ 78 kbps)

Wire Type: AWG22 to AWG16 stranded (use twisted pair wiring and copper conductors for network)

Neuron®: 3150, 10 MHz

**POWER SUPPLY**

Controller: 2.0 A, 24 VAC, 50-60 Hz, or 24 VDC

Fuse: 2.5 A slow-blow (Bussman GMD-2.0A, Littelfuse 23902.0A)

Rectifier: Half-wave

**MECHANICAL**

Operating Temperature: 32°F to 122°F (0°C to 50°C)

Relative Humidity: 5% to 95% RH (non-condensing)

Weight: 15 oz. (420 grams)

Enclosure Dimensions: 0.8" x 5" x 5.8" (20.3mm x 127mm x 147mm)

Enclosure Material: Metal

Mounting: Four sheet metal screws, optional DIN rail adaptor (part # 50-0550)

**AGENCY LISTINGS AND REGULATORY COMPLIANCE**

Class II device (when powered by a class II supply)

CSA 22.2 #205-M1983, #950-M89

UL916 certification for Energy Management Equipment

Part 15, Class B of the FCC Rule for Radio Frequency Devices

EMC Directive 89/336/EEC

LonMark 3.4 Certified, Functional Profile: 8508 Space Comfort Controller



**EFFICIENT BUILDING AUTOMATION CORPORATION**

401 – 8342 130<sup>th</sup> Street, Surrey BC, Canada V3W 8J9

Telephone: +1 604.248.4404 Facsimile: +1 604.248.4405

Website: [www.circon.com](http://www.circon.com)



Specifications subject to change without notice.

Circon™ is a trademark of Efficient Building Automation Corporation. Echelon®, LonWorks®, Neuron®, and LNS® are trademarks of Echelon Corporation registered in the United States and other countries. Windows® is a trademark of Microsoft Corporation registered in the United States and other countries. LonMark® and the LonMark logo are managed, granted and used by LonMark International under a license granted by Echelon Corporation. Tridium® and NiagaraAX® are trademarks of Tridium Inc. registered in the United States and other countries.

DOCUMENT # 80-0424 / REVISION 2.0 / PRINTED IN CANADA