

22-POINT FULLY PROGRAMMABLE HVAC CONTROLLER

OVERVIEW

The HVAC building automation controls market requires a DDC controller that provides scalable, consolidated control in a fully programmable, feature-rich LonMark® certified or Niagara^{AX} device.

Efficient Building Automation Corporation's Circon™ **UHC-300** controller unites a variety of configurable control blocks, combined with the power of the Circon BASIC programming language, to provide exceptional application flexibility. The UHC-300 is all you need in a 22-point DDC controller.

APPLICATIONS

The UHC-300 can be used to implement tailored control applications for unique or custom HVAC mechanical designs. The UHC-300's 12 universal inputs, 10 universal outputs, and control blocks are easily configured using Windows®-based software. Flexible alarm, trend, schedule, and PID control blocks can be used to quickly create effective control and monitoring solutions.

Along with the configurable control blocks and the input/output points, EBAC's powerful Circon BASIC programming language can be used to implement more complicated control sequences. Circon BASIC is flexible and powerful, allowing the user to create tailored control sequences for chilled water systems, condenser loops, heating water systems, packaged air handling units, built up air handling units or any custom HVAC mechanical design.

EBAC's no-cost Windows-based configuration software for the UHC-300 and the Circon BASIC Compiler are fully compatible with Echelon Corporation's LNS® and Tridium® Inc.'s Niagara^{AX} platforms.

ORDERING INFORMATION

Part number: 10-0367



FEATURES

- LonMark Certified, with easy-to-use LNS plug-ins for seamless integration into interoperable LonWorks® networks
- Fast and easy-to-use Tridium Niagara^{AX} wizards for seamless integration into interoperable Niagara networks
- Fully programmable with flexible and easy-to-use Circon BASIC programming language
- 12 universal inputs configurable for voltage, current, resistance and dry contacts
- 10 universal outputs configurable for voltage, current and digital
- Onboard real-time clock allows for time-based events, data logging and network master operation
- All memory is protected with a lithium battery
- Quick network access through an audio jack
- Auxiliary 15 VDC output for powering peripheral devices
- Adaptable for standalone applications or as part of a networked operation



SPECIFICATIONS

I/O CAPABILITY

12 Universal Inputs: 10 kΩ thermistor, 1 kΩ RTD, 4-20 mA current, 0-10 VDC, digital (dry contact)
 10 Universal Outputs: 4-20 mA current, 0-10 VDC, digital. Maximum drive of 100 mA per output.

COMMUNICATIONS

Transceiver: Echelon Free Topology Transceiver (FTT-10A @ 78 kbps)
 Wire Type: AWG22 to AWG16 stranded (use twisted pair wiring and copper conductors for network)
 Neuron®: 3150, 10 MHz

POWER SUPPLY

Controller: 2.0 A, 24 VAC, 50-60 Hz, or 24 VDC
 External Loads: 15 VDC output terminal provides 300 mA maximum
 Fuse: 2.5 A slow-blow (Bussman GMD-2.5A, Littelfuse 23902.5A)
 Power Fail Protection: Lithium battery retains data in RAM and clock

MECHANICAL

Operating Temperature: 32°F to 122°F (0°C to 50°C)
 Relative Humidity: 5% to 95% RH (non-condensing)
 Weight: 1 lb. 6 oz. (617 grams)
 Enclosure Dimensions: 1.9" x 5" x 10.3" (48mm x 127mm x 262mm)
 Enclosure Material: PVC, inflammability class V0 (UL94)
 Wire Type: AWG22 to AWG16 stranded; use copper conductors only
 Mounting: DIN rail

AGENCY LISTINGS AND REGULATORY COMPLIANCE

Class II device (when powered by a class II supply)
 CSA 22.2 #205-M1983, #950-M89
 UL916 certification for Energy Management Equipment
 Part 15, Part J, Class A of the FCC Rule for Radio Frequency Devices
 EMC Directive 89/336/EEC
 LonMark 3.3 Certified



EFFICIENT BUILDING AUTOMATION CORPORATION

401 – 8342 130th Street, Surrey BC, Canada V3W 8J9
 Telephone: +1 604.248.4404 Facsimile: +1 604.248.4405
 Website: www.circon.com



Specifications subject to change without notice.

Circon™ is a trademark of Efficient Building Automation Corporation. Echelon®, LonWorks®, Neuron®, and LNS® are trademarks of Echelon Corporation registered in the United States and other countries. Windows® is a trademark of Microsoft Corporation registered in the United States and other countries. LonMark® and the LonMark logo are managed, granted and used by LonMark International under a license granted by Echelon Corporation. Tridium® and NiagaraAX® are trademarks of Tridium Inc. registered in the United States and other countries.

DOCUMENT # 80-0248 / REVISION 2.0 / PRINTED IN CANADA